




6SK7, 6SK7-GT/G

delete
10/64

6SK7
6SK7-GT/G

TRIPLE-GRID SUPER-CONTROL AMPLIFIER

Heater	Coated Unipotential Cathode	
Voltage	6.3	a-c or d-c volts
Current	0.3	amp.
	6SK7	6SK7-GT/G
Direct Interelectrode Cap.	▲	▲▲
Grid to Plate	0.003 max.	0.005 max. μ mf
Input	6.0	6.5 μ mf
Output	7.0	7.5 μ mf
Maximum Overall Length	2-5/8"	3-5/16"
Maximum Seated Height	2-1/16"	2-3/4"
Maximum Diameter	1-5/16"	1-5/16"
Bulb	Metal Shell, MT-8	T-9
Base	{ Small Wafer Octal 8-Pin	{ Small Wafer Octal 8-Pin, Sleeve
Basing Designation	8N	GT-8N
Pin 1 { 6SK7, Shell 6SK7-GT/G, Base Sleeve		Pin 4 - Grid
Pin 2 - Heater		Pin 5 - Cathode
Pin 3 - Suppressor		Pin 6 - Screen
Pin 7 - Heater		Pin 8 - Plate
Mounting Position	Any	Any

BOTTOM VIEW

Maximum And Minimum Ratings Are Design-Center Values

AMPLIFIER

Plate Voltage	300 max.	volts
Screen Voltage	125 max.	volts
Screen Supply Voltage	300 max.	volts
Grid Voltage	0 min.	volts
Plate Dissipation	4.0 max.	watts
Screen Dissipation	0.4 max.	watt
Typical Operation and Characteristics - Class A ₁ Amplifier:		
Plate	100	250 volts
Screen	100	100 volts
Grid	-1	-3 volts
Suppressor	Connected to cathode at socket	
Plate Res.	0.12	0.8 approx. megohm
Transconc.	2350	2000 μ hos
Grid Bias for		
transcond. of 10 μ hos	-35	-35 volts
Plate Cur.	13	9.2 ma.
Screen Cur.	4.0	2.6 ma.

■ In circuits where the cathode is not connected directly to the heater, the potential difference between heater and cathode should be kept as low as possible.

▲ With shell connected to cathode.

▲▲ With shield connected to cathode.

Dec. 1, 1942

RCA RADOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.


DATA

6SK7



6SK7

AVERAGE PLATE CHARACTERISTICS



JUNE 24, 1938

RCA RADOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.

92C-4940




6SK7

Prostate
10/64

6SK7

AVERAGE CHARACTERISTICS



JUNE 23, 1938

RCA RADIODOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.

92C-4938